

# PQ Type 电子变压器 Power transformer



## ■ 特点 Features

- 工作频率: 1kHz~10MHz
- 工作温度: -20℃~+100℃
- 按客户需求设计定制
- 符合UL和VDE安规要求
- Operation Frequency from 1kHz to 10MHz
- Operating Temperature: -20℃~+100℃
- Can be designed to customer requirements
- Can meet UL and VDE safety requirements

## ■ 主要用途 Typical Applications

- 适用于功率电源供应器
- 适用于太阳能, 驱动电源, 电脑电视, 网络适配器等
- Designed for power solutions
- Designed for solar inverter, power adapter, PC, LED power, networking etc.

## ■ 典型规格 Typical Specifications

- 绝缘等级: B/F
- 推荐储存温度: -20℃~+55℃
- Insulation Grade: class B/F
- Recommended Storage Temperature: -20℃~+55℃

型号 Type	功率 Power Capacity (W)		频率 Frequency (Hz)	尺寸 Size (L*W*H) (mm)
	Forward	Flyback		
PQ 20/16	70	45	1k-10M	24.0×25.0×19.0
PQ 20/20	90	65		24.0×24.6×26.0
PQ 26/16	170	110		29.0×30.3×23.5
PQ 26/25	195	120		29.0×30.5×30.5
PQ 30	225	150		33.5×49.0×14.5
PQ 32/20	230			33.5×35.0×22.0
PQ 32/25	300			34.5×36.0×26.5
PQ 32/30	330			34.5×35.0×34.0
PQ 35/35	450			36.5×40.5×50.0